APPLICATION: 3 Axle 4S2M SIDE BY SIDE HALDEX SELECT FFV

PART #: PAK4S2MS-3-HR


CONTENTS: Glad hand assemblies


Air tank with installed drain valve and plugged unused ports Air tank mounting kit with pads, bolts, washers and lock nuts Brake valve(s) are installed and include push to connect fittings Hoses with swivel hose ends are installed to valve(s) Four speed sensors, sensor bushings and sensor extensions Hose separators and sensor cable retainers

Service Supply

SPECIFY YOUR HOSE LENGTHS BELOW 9.5" Diameter 1488 Cubic Inch 27.5" Mount Centers







	FY HOSE LENGTH IN INCHES GENCY:	S
E1R	E1C	
E2R	E2C	
E3R	E3C	
SERVI	CE:	
S1R	S1C	
S2R	S2C	
S3R	S3C	
S4R	S4C	
	<u> </u>	
	Service Hose Supply Ho	ose

Specifications:

ABS100

Hoses meet J1402 & JT106 specifications and are 3/8 ID unless otherwise noted. Reservoirs meet J10B specifications Pipe fittings are brass or plated SH80 steel. Push-in style 3/8 tube fittings standard. ABS Electronics pre-tested before shipment.

12 Inch Diameter 2880 Cubic Inch 29.5" Mount Centers ABS150CB (N9002CB)

Service Tube